EN125





The EN125 is perfect for urban and extra urban rides, it assures reliability and resistance. It is well characterized as one of the best productivity for 125cc 4-stroke engine.



Colors availables









Engine type Single cylinder, 4-stroke, SOHC

124 Displacement (cc) Cooling system Air-cooled Compression ratio 9,2:1 12,0 / 9500 Maximum power (hp / rpm) NC

Maximum torque (N.m / rpm)

Kick and electric starter Starter system Lubrification system Wet sump

Ignition system CDI Fuel delivery Carburetor

CHASSIS

Frame Steel cradle

Telescopic fork, coil spring, oil damped Front suspension system Rear suspension system Swingarm link type, coil spring, oil damped

Front brake Drum Rear brake Drum Wheels Spoke

MOTORS Front tyre 2,75-18 4PR Rear tyre 3-18 52P

114

14

5-speed constant mesh



DIMENSIONS

Overall dim - L x w x h (mm) 1920*735*1070

Wheelbase (mm) 1265 735 Seat height (mm) Min ground clearance (mm) 160



TRANSMISSION



WEIGHT/CAPACITIES



Transmission system



EQUIPMENTS











Always wear a helmet, eye protection and protective proper clothing.

For more information, please contact your dealer Suzuki 2R.

Suzuki 2R encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

